## Monadnock Envi® Wallgraphics

An ENVIPORTFOLIO Product

Envi Wallgraphics offer a renewable fiber-based 10% PCW alternative to vinyl for walls, windows and other rigid surfaces in the home and in commercial settings/environments.

Envi Wallcovering meets the strict California 01350 standards for indoor air quality - a prerequisite for LEED credit qualification, and carries a class "A" fire rating based on ASTM E-84 standard testing for smoke generation and flame spread. Envi is easy to clean and sanitize.

Specify bright white Envi Wallgraphics when looking to boldly enhance a small space or an entire establishment in an eco-conscious way.



## Performance

- Breathable to reduce mold & mildew
- · Prepasted water activated adhesive
- Strippable with ease
- Washable & Scrubbable
- UV & Latex Inkjet Compatible
- Meets California 01350 standards for air quality
- REACH, Lacey Act, CPSIA & RohS compliant

Typical Properties	UOM	C2896-108	C2896-148
Basis Weight	lb./3,000f²	104	140
Basis Weight	g/m²	166	228
Caliper	mils / mm	6.7 / 0.17	9.6 / 0.24
Dry Tensile CD	pli / kN/m	37 / 6.48	38 / 6.65
Dry Tensile MD	pli / kN/m	45 / 7.88	55 / 9.63
Elmendorf Tear CD	grams	130	200
Elmendorf Tear MD	grams	125	190
Sheffield Smoothness	SU	15	18
Color	L/a/b	95.5/-0.3/2.8	95.5/-0.3/2.8
Parker Print Surf		1.3	1.4
Opacity	%	96	97.9
Gloss (75 degrees)	GU	15	13

Appropriate FSC On Product Logo:





Monadnock Paper Mills, Inc. 117 Antrim Road, Bennington, NH 03442 www.mpm.com | 800.221.2159 06.25

## Made with the Environment in Mind

- The FSC logo ensures responsible use of forest resources certified by a third party
- Made with third-party Green-e® certified Wind Power Renewable Energy Certificates
- Manufactured Carbon Neutral with Verified Emission Reductions certified under the Climate Action Reserve Protocol
- Manufactured Process Chlorine Free
- Manufactured under an ISO 14001:2004 Certified Environmental Management System

Installation instructions and warranty are available at www.mpm.com/enviwallgraphics.

